



Loading capacity (ratio 1:20 – European):	14 Kg
Heating:	Electric
Load diameter (mm):	560
Voltage:	3x400V+N 50Hz
Heating power (Kw):	18

Machine dimension (WxDxH - mm):	791x874x1610
Net weight (Kg):	213
Packing dimension (WxDxH - mm):	840x890x1890
Gross weight (Kg):	225

- ☑ Episodic painted panels;
- ☑ Drum in stainless steel AISI 304.
- ☑ Ease of loading and unloading thanks to the large door opening angle (180°) and the big load diameter.
- ☑ On request, left opening;
- ☑ Easy access to the lint screen;
- ☑ Lint screen request displayed;
- ☑ A safety device stops the dryer if the door is opened while the dryer is working;
- ☑ IM7 Microprocessor: thanks to the use of icons, and to the possibility to dialog in more languages, the user can easily manage the drying temperature and time. The 30 available programs can be easily modified and named;
- ☑ Cooling cycle at the end of the program to avoid linen shocks;
- ☑ No wrinkle cycle to make easier the linen ironing;
- ☑ Easy maintenance thanks to the self diagnostic function with the following error displaying. The HELP area is reserved to the technician who can find there the trouble shooting of the most common error. The main devices correct working can be tested directly from the keypad.
- ☑ Management cost control: the total and partial consumption may be displayed.
- ☑ Reversing drum function to assure a uniform drying of the biggest linen (option)
- ☑ Power Control: the dryer can work on more power level (optional).
- ☑ Drum Speed Control: the drum speed can be controlled by the user from the key pad (option – only if the reversing drum option is present).
- ☑ Fan Speed Control: the suction fan speed can be controlled by the user from the key pad (option – only if the reversing drum option is present).



Note: technical data and characteristics may be changed without any previous notice.



Loading capacity (ratio 1:20 – European):	10 Kg
Heating:	Gas
Load diameter (mm):	560
Voltage:	3x400V+N 50Hz
Heating power (Kw):	29,4

Machine dimension (WxDxH - mm):	791x874x1610
Net weight (Kg):	212
Packing dimension (WxDxH - mm):	840x890x1890
Gross weight (Kg):	224

- ☑ Eposidic painted panels;
- ☑ Drum in stainless steel AISI 304.
- ☑ Ease of loading and unloading thanks to the large door opening angle (180°) and the big load diameter.
- ☑ On request, left opening;
- ☑ Easy access to the lint screen;
- ☑ Lint screen request displayed;
- ☑ A safety device stops the dryer if the door is opened while the dryer is working;
- ☑ IM7 Microprocessor: thanks to the use of icons, and to the possibility to dialog in more languages, the user can easily manage the drying temperature and time. The 30 available programs can be easily modified and named;
- ☑ Cooling cycle at the end of the program to avoid linen shocks;
- ☑ No wrinkle cycle to make easier the linen ironing;
- ☑ Easy maintenance thanks to the self diagnostic function with the following error displaying. The HELP area is reserved to the technician who can find there the trouble shooting of the most common error. The main devices correct working can be tested directly from the keypad.
- ☑ Management cost control: the total and partial consumption may be displayed.
- ☑ Reversing drum function to assure a uniform drying of the biggest linen (option)
- ☑ Power Control: the dryer can work on more power level (optional).
- ☑ Drum Speed Control: the drum speed can be controlled by the user from the key pad (option – only if the reversing drum option is present).



Note: technical data and characteristics may be changed without any previous notice.



Loading capacity (ratio 1:20 – European):	10 Kg
Heating:	Steam
Load diameter (mm):	560
Voltage:	3x400V+N 50Hz
Heating power (Kw):	44,4

Machine dimension (WxDxH - mm):	791x874x1610
Net weight (Kg):	219
Packing dimension (WxDxH - mm):	840x890x1890
Gross weight (Kg):	229

- ☑ Eposidic painted panels;
- ☑ Drum in stainless steel AISI 304.
- ☑ Ease of loading and unloading thanks to the large door opening angle (180°) and the big load diameter.
- ☑ On request, left opening;
- ☑ Easy access to the lint screen;
- ☑ Lint screen request displayed;
- ☑ A safety device stops the dryer if the door is opened while the dryer is working;
- ☑ IM7 Microprocessor: thanks to the use of icons, and to the possibility to dialog in more languages, the user can easily manage the drying temperature and time. The 30 available programs can be easily modified and named;
- ☑ Cooling cycle at the end of the program to avoid linen shocks;
- ☑ No wrinkle cycle to make easier the linen ironing;
- ☑ Easy maintenance thanks to the self diagnostic function with the following error displaying. The HELP area is reserved to the technician who can find there the trouble shooting of the most common error. The main devices correct working can be tested directly from the keypad.
- ☑ Management cost control: the total and partial consumption may be displayed.
- ☑ Reversing drum function to assure a uniform drying of the biggest linen (option)
- ☑ Power Control: the dryer can work on more power level (optional).
- ☑ Drum Speed Control: the drum speed can be controlled by the user from the key pad (option – only if the reversing drum option is present).
- ☑ Fan Speed Control: the suction fan speed can be controlled by the user from the key pad (option – only if the reversing drum option is present).



Note: technical data and characteristics may be changed without any previous notice.